

PLUG BODY (STYLE S)

Dimensions (inches [millimeters]):

- Top thickness: .017 [0.43]
- Top width: .311 [7.90]
- Top hole diameter: .153 [3.89]
- Top hole spacing: .200 [5.08]
- Top hole diameter: .050 [1.27] TYP.
- Top hole spacing: .100 [2.54] TYP.
- Top hole diameter: .100 [2.54] TYP.
- Top hole spacing: .050 [1.27] TYP.
- Top hole diameter: .124 [3.15]
- Top hole spacing: 2.000 [50.80]
- Top hole spacing: 2.400 [60.96]
- Top hole spacing: 4.800 [121.92]
- Top hole spacing: 5.106 [129.69]
- Top hole diameter: .154 [3.91]

RECEPTACLE BODY (STYLE F)

Dimensions (inches [millimeters]):

- Top thickness: .017 [0.43]
- Top width: .311 [7.90]
- Top hole diameter: .153 [3.89]
- Top hole spacing: .200 [5.08]
- Top hole diameter: .050 [1.27] TYP.
- Top hole spacing: .100 [2.54] TYP.
- Top hole diameter: .100 [2.54] TYP.
- Top hole spacing: .050 [1.27] TYP.
- Top hole diameter: .114 [2.90]
- Top hole spacing: 2.000 [50.80]
- Top hole spacing: 2.400 [60.96]
- Top hole spacing: 4.800 [121.92]
- Top hole spacing: 5.106 [129.69]
- Top hole diameter: .441 [11.20]

27